


- 79 - Fire-rated hatch
- 80 - Tread
- 86 - Hinge
- 88 - Side bracket
- 90 - LXH handrail
- 93 - LXS stile end
- 94 - Stringer (ladder side element)
- 714 - Fire-resistant sealant
- 715 - Insulation: rock wool with a min. density of 2.5lb/ft³
- 716 - Spacing washer
- 765 - Plastic trims LXL-PVC (US)

Step length	E	13 1/4"
Step width	S	3 1/8"
Step thickness	Z	7/8"

LWF II		22 1/2" x 47"	25" x 47"	22 1/2" x 54"	25" x 54"	30" x 54"
Ceiling height	H	7'5" - 8'11"		7'11 1/2" - 10'1"		
Rough opening	A x B	22 1/2" x 47"	25" x 47"	22 1/2" x 54"	25" x 54"	30" x 54"
Outside frame dimensions	W x L	22" x 46 5/8"	24 1/2" x 46 5/8"	22" x 53 1/2"	24 1/2" x 53 1/2"	29 1/2" x 53 1/2"
Internal dimensions	M x N	20 1/2" x 44 7/8"	23" x 44 7/8"	20 1/2" x 51 1/4"	23" x 51 1/4"	28" x 51 1/4"
Projection	R	67"		73 1/4"		
Landing space	C	59"		65 1/4"		
Folded ladder height	K	15"				
Board movement after opening	P	1"				
Distance between steps	G	9 7/8"		10 1/2"		
Frame height		8 5/8"				
Approx. Weight (kg)		103	107	111	115	126



LWF



Technical drawing:
The LWF Loft Ladder

FORMAT:
A4

SCALE:
1:20/1:10

DATE:
04.2016

Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.